

MOKON® SCREW TEMPERATURE REGULATION UNIT 9 KW, 6 GPM

TC35, TC50, TC55, TC65, TC80, TP93

Features:

- Unique serpentine heating chamber for highest rates of heat transfer efficiency.
- "By Pass" cooling philosophy eliminates thermal shock on the heat exchanger, minimizes mineral deposits, and provides a longer service life.
- High-pressure and low-pressure safety shut-off switches.
- Pressure relief valve to protect the filter, heat exchanger, and heaters from process blockage.
- Air purge valve eliminates air in the system and lengthens the heat transfer fluid life.
- Stainless steel braided hoses used wherever possible for ease of maintenance.

Specifications:

Heat Transfer Fluid:	Calflo AF, Duratherm 600, Duratherm G, Ucon HTF 500, Paratherm, Multitherm PG-1, IG-2, Xceltherm 600
Tank Construction:	Stainless Steel with Brass Sight Glass 1/2" Breather / Fill Port 1/2" FNPT Drain Port
Tank Capacity:	4.6 Gallons
Heating Capacity:	9 KW
Heat Exchanger:	1.4 Sq. Ft. Shell and Tube Construction Water Connections: 1/2" FNPT
Cooling Water:	50 Deg. F. Min.; 90 Deg. F. Max. 5 GPM Min.; 10 GPM Max. 30 PSI Min.; 100 PSI Max. 1/2" FNPT Connections
Pump:	3/4 HP Spur Gear, 10 GPM Cast Iron Construction
Gage Package:	Supply Pressure, Filter Inlet Pressure, Left Screw Return Pressure, Right Screw Return Pressure
Dimensions:	25" D x 29.5" W x 17" T

To/From Process

Connections: 1/2" FNPT

Filter: 100 Micron

Coil Voltage: 24 VDC Standard / 120 VAC Special

Electrical Supply: 230 VAC / 460 VAC

Paint: Durable Powder Coat Finish
Dark Gray, CM5106, RAL 7016

Notes:

- The existing temperature controls to be used to operate the new unit.
- Heat exchanger, supply and return connections, to be made by the customer.
- Installation is the responsibility of the customer.
- Installation assistance can be contracted through our Field Service Group.

In order for us to best serve you, please provide the following information:

- The serial number of the extruder that will be retrofitted so that proper engineering review can be made.
- Confirm the coil voltage. There is an up charge for 120 VAC coils.
- Note if this unit will be under the base or setting along side of the extruder.
- Estimate the number and length of the braided stainless-steel hoses needed. Hoses sold separately.
Number _____ Length _____

For over 30 years, Cincinnati Milacron has been the leader in cutting-edge extrusion process technology. Today, our seasoned Extrusion Aftermarket experts are dedicated to applying the same emerging technology to your existing extrusion equipment, as well.

**We have the wide breadth of products;
we have the expertise; now it's time to bring your existing extrusion equipment up to today's standards.**

**EXTRUSION
AFTERMARKET**

3203 9SO
7.1.05

Milacron Inc • 4165 Halfacre Rd • Batavia, Ohio 45103
513-536-3314 • fax 513-536-2668 • <http://plastics.milacron.com>



**CINCINNATI
MILACRON**

Twin Screw Extrusion Systems



**AKRON
MILACRON**

Single Screw Extrusion Systems

