



MAXIMA MM

950 WP

CLAMP UNIT SPECIFICATIONS

	English		Metric	
	Unit	Value	Unit	Value
Clamp Force	tons	955	kN	8500
Clamp Opening Force	tons	43	kN	382
Clamp Stroke	in.	72.8	mm	1850
Clamp Speed Open	in./sec.	38	mm/sec.	965
Clamp Speed Close	in./sec.	32	mm/sec.	813
Maximum Daylight	in.	88.6	mm	2250
Min/Max Mold Thickness	in.	15.7 / 47.2	mm	400 / 1200
Maximum Mold Weight	lbs.	38,000	kgs	17234
Platen Size (H x V)	in.	70.9 x 58.3	mm	1800 x 1480
Distance Between Tie Rods (H x V)	in.	54.7 x 42.1	mm	1390 x 1070
Tie Rod Diameter	in.	7.67	mm	195
Ejector Stroke (Max)	in.	9.8	mm	250
Ejector Force @2000 psi	tons	20.5	kN	182

MACHINE SPECIFICATIONS

	English		Metric	
	Unit	Value	Unit	Value
Overall Length (w/ 3470 IU)	in.	383.0	mm	9732
Overall Width	in.	118.0	mm	2997
Overall Height	in.	136.7	mm	3472
Shipping Weight (without oil)	lbs.	101,260	kg	46027
Hydraulic System Pressure	psi	2,950	bar	203
Variable Volume Pump Capacity	gpm	65	L/min	246
Fixed Pump Capacity	gpm	121	L/min	458
Injection and Extruder	gpm	165	L/min	625
Eject and Core Pull	gpm	21	L/min	79
Electric Motor	hp	150	kw	112
Total Oil Reservoir Capacity	gal	350	L	1325
Heat Exchanger Water @85° F	gpm	41	L/min	155



MAXIMA MM 950 WP

INJECTION UNIT SPECIFICATIONS

	English	A	B	C	Metric	A	B	C
Injection Capacity Maximum								
G.P. Styrene (theoretical)	oz	46	60	76	g	1304	1701	2155
Displacement	in ³	84.5	110.4	139.8	cm ³	1385	1810	2290
Injection Pressure Maximum	psi	33,200	27,800	21,900	bar	2290	1917	1510
Injection Rate - Standard	in ³ /sec	44	57	73	cm ³ /sec	721	934	1196
Injection Rate - MAXIMA PLUS	in ³ /sec	82	107	135	cm ³ /sec	1434	1753	2212
Screw Stroke	in	14.2	14.2	14.2	mm	360	360	360
Screw Diameter	in	2.76	3.15	3.54	mm	70	80	90
Screw L/D		22.0	22.8	20.0		22.0	22.8	22.0
Low Torque Screw Speed Maximum	rpm	289	253	225	rpm	289	253	225
Low Torque at Screw	in-lb	26,900	26,900	26,900	Nm	3037	3037	3037
	@ psi	2,900	2,900	2,900	@ bar	200	200	200
Recovery Rate (GP Styrene) calculated	oz/sec	3.2	4.0	4.7	gr/sec	90	115	134
High Torque Screw Speed Maximum	rpm	289	253	225	rpm	289	253	225
High Torque at Screw	in-lb	40,700	40,700	40,700	Nm	4595	4595	4595
	@ psi	2,900	2,900	2,900	@ bar	200	200	200
Recovery Rate (GP Styrene) calculated	oz/sec	3.2	4.0	4.7	gr/sec	90	115	134
Number of Pyrometers (barrel/nozzle)		4 / 1	4 / 1	4 / 1		4 / 1	4 / 1	4 / 1
Total Heat Capacity	kW	35.8	41.2	41.2	kW	35.8	41.2	41.2

INJECTION UNIT SPECIFICATIONS

	English	A	B	Metric	A	B
Injection Capacity Maximum						
G.P. Styrene (theoretical)	oz	85	105	g	2410	2977
Displacement	in ³	155.3	191.7	cm ³	2545	3142
Injection Pressure Maximum	psi	27,800	22,500	bar	1917	1552
Injection Rate - Standard	in ³ /sec	58	71	cm ³ /sec	950	1163
Injection Rate - MAXIMA PLUS	in ³ /sec	135	167	cm ³ /sec	2212	2736
Screw Stroke	in	15.7	15.7	mm	400	400
Screw Diameter	in	3.54	3.94	mm	90	100
Screw L/D		22.0	20.0		22.0	20.0
Low Torque Screw Speed Maximum	rpm	225	202	rpm	225	202
Low Torque at Screw	in-lb	36,100	36,100	Nm	4076	4076
	@ psi	2,900	2,900	@ bar	200	200
Recovery Rate (GP Styrene) calculated	oz/sec	4.7	5.8	gr/sec	134	164
High Torque Screw Speed Maximum	rpm	225	202	rpm	225	202
High Torque at Screw	in-lb	54,800	54,800	Nm	6187	6187
	@ psi	2,900	2,900	@ bar	200	200
Recovery Rate (GP Styrene) calculated	oz/sec	4.7	5.8	gr/sec	134	164
Number of Pyrometers (barrel/nozzle)		4 / 1	4 / 1		4 / 1	4 / 1
Total Heat Capacity	kW	53.8	53.8	kW	53.8	53.8

MAXIMA MM 950 WP

INJECTION UNIT SPECIFICATIONS

	English	A	B	Metric	A	B
Injection Capacity Maximum						
G.P. Styrene (theoretical)	oz	116	140	g	3289	3969
Displacement	in ³	210.9	255.2	cm ³	3456	4181
Injection Pressure Maximum	psi	27,700	22,900	bar	1910	1579
Injection Rate - Standard	in ³ /sec	58	70	cm ³ /sec	950	1147
Injection Rate - MAXIMA PLUS	in ³ /sec	136	165	cm ³ /sec	2228	2703
Screw Stroke	in	17.3	17.3	mm	440	440
Screw Diameter	in	3.94	4.33	mm	100	110
Screw L/D		22.0	20.0		22.0	20.0
Low Torque Screw Speed Maximum	rpm	202	184	rpm	202	184
Low Torque at Screw	in-lb	48,200	48,200	Nm	5442	5442
	@ psi	2,900	2,900	@ bar	200	200
Recovery Rate (GP Styrene) calculated	oz/sec	5.8	6.6	gr/sec	164	188
High Torque Screw Speed Maximum	rpm	202	184	rpm	202	184
High Torque at Screw	in-lb	82,400	82,400	Nm	9303	9303
	@ psi	2,900	2,900	@ bar	200	200
Recovery Rate (GP Styrene) calculated	oz/sec	5.8	6.6	gr/sec	164	188
Number of Pyrometers (barrel/nozzle)		4 / 1	4 / 1		4 / 1	4 / 1
Total Heat Capacity	kW	56.0	56.0	kW	56.0	56.0

INJECTION UNIT SPECIFICATIONS

	English	A	B	Metric	A	B
Injection Capacity Maximum						
G.P. Styrene (theoretical)	oz	178	230	g	5046	6521
Displacement	in ³	324.8	419.4	cm ³	5322	6872
Injection Pressure Maximum	psi	27,500	21,200	bar	1897	1462
Injection Rate - Standard	in ³ /sec	52	67	cm ³ /sec	852	1098
Screw Stroke	in	22.0	22.0	mm	560	560
Screw Diameter	in	4.33	4.92	mm	110	125
Screw L/D		22.7	20.0		22.7	20.0
Low Torque Screw Speed Maximum	rpm	181	162	rpm	181	162
Low Torque at Screw	in-lb	69,500	69,500	Nm	7847	7847
	@ psi	2,300	2,300	@ bar	159	159
Recovery Rate (GP Styrene) calculated	oz/sec	6.5	8.2	gr/sec	184	234
High Torque Screw Speed Maximum	rpm	116	116	rpm	116	116
High Torque at Screw	in-lb	107,800	107,800	Nm	12171	12171
	@ psi	2,300	2,300	@ bar	159	159
Recovery Rate (GP Styrene) calculated	oz/sec	4.2	5.9	gr/sec	118	167
Number of Pyrometers (barrel/nozzle)		4 / 1	4 / 1		4 / 1	4 / 1
Total Heat Capacity	kW	61.2	61.2	kW	61.2	61.2